

## LIGHTWEIGHT IMPACT WRENCH TORQUE LIMITED



an excellent weight/power ratio. The are especially developped for the tireshop applications. The Twin Hammer impact mechanism gives high energy levels per impact en thus suitable for heavy duty applications. The energy is directly transmitted to the anvil for maximum power and low maintenance. The tools are limiting the tightening torque to 90 Nm for wheel nut applications, so overtightening is history! Full power available in loosening direction. Allways use the torque wrench to check the torque!

These composite impact wrenches by RED ROOSTER have

## CHARACTERISTICS:

- Ergonomic design, well balanced
- Compact and lightweight
- Impact mechanism Twin Hammer
- Exhaust silenced, through grip



ACCESSORIES

EXHAUST HOSE ASSEMBLY

ORDER NO.: EH-43-4033SUB

Туре	Brand	Square drive	Type 1)	Bolt capacity mm	Impact- mechanism	RPM	Torque Nm	Power adjustment	Air- cons. I/s	Weight kg	Inlet- thread	Hose- diameter mm	Vibration m/s²	Noise level dB(A)	
RR-16N T	RR	1/2"	R	14	Twin-Hammer	11.000	405	R: ±90 Nm	5	1,2	PT 1/4"	6,5	4,6	83	
RR-18N T	RR	1/2"	R	16	Twin-Hammer	7.000	815	R: ±90 Nm	8,2	2	PT 1/4"	10	3,1	83	

<sup>1)</sup> Type: R = ring type